BOESCH

www.BoeschPumps.com

BOOSTER SYSTEMS



GE 1.5B PERFORMANCE CURVE

Pump Performance Datasheet

Operating Conditions	
Flow, rated	: 135.0 USgpm
Differential head / pressure, rated (requested)	: 184.0 ft
Differential head / pressure, rated (actual)	: 187.9 ft
Suction pressure, rated / max	: 0.00 / 0.00 psi.g
NPSH available, rated	: Ample
Site Supply Frequency	: 60 Hz

Performance	
Speed criteria	: Synchronous
Speed, rated	: 3600 rpm
Impeller diameter, rated	: 6.81 in
Impeller diameter, maximum	: 7.10 in
Impeller diameter, minimum	: 5.00 in
Efficiency	: 68.81 %
NPSH required / margin required	: 5.78 / 0.00 ft
Ns (imp. eye flow) / Nss (imp. eye flow)	: 1,038 / 9,215 US Units
MCSF	: -
Head, maximum, rated diameter	: 191.2 ft
Head rise to shutoff	: 3.89 %
Flow, best eff. point	: 201.6 USgpm
Flow ratio, rated / BEP	: 66.97 %
Diameter ratio (rated / max)	: 95.95 %
Head ratio (rated dia / max dia)	: 88.83 %
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00
Selection status	: Acceptable

Liquid	
Liquid type	: Chemical
Additional liquid description	:
Solids diameter, max	: 0.00 in
Solids concentration, by volume	: 0.00 %
Temperature, max	: 68.00 deg F
Fluid density, rated / max	: 1.000 / 1.000 SG
Viscosity, rated	: 1.00 cP
Vapor pressure, rated	: 0.00 psi.a

Material	
Material selected	: Standard

Pressure Data	
Maximum discharge pressure	: 82.75 psi.g
Maximum allowable working pressure	: N/A
Maximum allowable suction pressure	: N/A
Hydrostatic test pressure	: N/A

Driver & Power Data (@Max density)	
Driver sizing specification	: Rated power
Margin over specification	: 0.00 %
Service factor	: 1.00
Power, hydraulic	: 6.27 hp
Power, rated	: 9.12 hp
Power, maximum, rated diameter	: 13.22 hp
Minimum recommended motor rating	: 10.00 hp / 7.46 kW




65.000 in
[1651.00 mm]
18.250 in
[463.55 mm]
NOT EXACT DRAWING, REFERENCE ONLY
Ø3"
Ø2"
Ø3"
41.540 in
[1055.12 mm]
11.660 in
[296.16 mm]
18.000 in
[457.20 mm]
8.795 in
[223.39 mm]
64.134 in
[1629.01 mm]
43.352 in
[1101.14 mm]
22.860 in
[580.64 mm]
59.055 in
[1500.00 mm]
3.000 in
[76.20 mm]
40.000 in
[1016.00 mm]
3.00
13.75
12.00
6.00
18.00





NOT EXACT DRAWING, REFERENCE ONLY